In the Claims:

Please amend claims 1, 6, 7, 9, 11, 15 and 18 to read as follows:

Mr.

1. (amended) A head massaging device comprising:

a plurality of resilient fingers, said fingers each having a free end and an opposite end, said opposite ends being coupled together; and

an electric vibrator coupled to said opposite ends whereby vibrations generated by said electric vibrator are transmitted from said opposite ends through said fingers to said free ends;

said fingers defining a head-receiving space for receiving a head, said space extending between said free ends and said opposite ends and having an opening at one end formed by a juxtaposition of said free ends of said fingers, said opening being smaller than said head, and at least a portion of said head-receiving space having a circumference which exceeds a circumference of said opening whereby, in use, when said device is lowered onto said head so that said head enters said head-receiving space through said opening, said free ends of said fingers apply pressure to and thus massage said head.

6. (amended) The device according to claim 1 further including a handle for gripping-said massaging device, said handle receiving said opposite ends of said fingers and housing said electric vibrator.

Bo

7. (amended) A head massaging device including at least:

a <u>plurality of resilient</u> and pliable fingers, said fingers each having a free end and an opposite end;

a vibrator coupled to said opposite ends whereby vibrations generated by said vibrator are transmitted along said fingers from said opposite ends to said free ends; and

said fingers defining a self-supporting head-receiving space for receiving a head, said space extending between said free ends and said opposite ends and having a self-maintained opening at one end formed by a juxtaposition of said free ends of said fingers, said opening being of a circumference smaller than a circumference of said head, whereby said head can fit inside said space with said free ends in contact with said head, and at least a portion of said head-receiving space having a

B2

circumference which is greater than said circumference of said opening whereby, in use, when said device is lowered on to said head so that said head enters said head-receiving space through said opening, said free ends of said fingers apply pressure to and thus massage said head.

B3

9. (amended) The device according to claim 8, wherein each said free end is terminated in a bulb or ball structure.

By

11. (amended) The device according to claim 10, wherein said fingers are electrically conductive.

15. (amended)\A head massaging device including at least:

a plurality of resilient fingers, said fingers each having a free end and an opposite end;

a vibrator coupled to said opposite ends whereby vibrations generated by said vibrator are transmitted along said fingers from said opposite ends to said free ends;

and a handle for receiving said opposite ends and in which is disposed said vibrator;

each of said fingers having a transversely extending portion immediately adjacent the handle, each said transversely extending portion being followed by a contiguous portion extending downwardly and inwardly from said transversely extending portion, said contiguous portion terminating in said free end, said intermediate length and continuous length of said fingers together defining a head-receiving space for receiving a head, said space extending between said free ends and said opposite ends and having an opening at one end formed by a juxtaposition of said free ends of said fingers, said opening having a circumference smaller than a circumference of said head, and at least a portion of said head-receiving space having a circumference which exceeds said circumference of said opening whereby, in use, when said device is lowered on to said head so that said head enters said head-receiving space through said opening, said free ends of said fingers apply pressure to and thus massage said head.

136

18. (amended) The device according to claim 17, wherein each said free end is terminated in a bulb or ball structure.

- 23. (new) A head massaging device comprising a plurality of resilient non-rotating fingers, said fingers each having a free end and an opposite end, said opposite ends being coupled together, said fingers defining a head-receiving space for receiving a head, said space extending between said free ends and said opposite ends and having an opening at one end formed by a juxtaposition of said free ends of said fingers, said opening being smaller than said head, and at least a portion of said head-receiving space having a circumference which exceeds a circumference of said opening; and an electric vibrator coupled to said opposite ends of said fingers whereby vibrations generated by said vibrating means are transmitted from said opposite ends through said fingers to said free ends whereby, in use, when said device is lowered onto said head so that said head enters said head-receiving space through said opening, said free ends of said fingers apply pressure to and thus massage said head.
- 24. (new) The device according to claim 23 further including a handle for receiving opposite ends of said fingers and which is disposed said vibrating means.
- 25. (new) The device according to claim 24, wherein said fingers are pliable so that the size and shape of said opening can be varied.
- 26. (new) A head massaging device including at least:
- a plurality of resilient and non-rotating fingers, said fingers each having a free end and an opposite end;
- a vibrator coupled to said opposite ends whereby said opposite ends are fixed relative to said vibrator and vibrations generated by said vibrator are transmitted along said fingers from said opposite ends to said free ends; and

said fingers defining a self-supporting head-receiving space for receiving a head, said space extending between said free ends and said opposite ends and having a self-maintained opening at one end formed by a juxtaposition of said free ends of said fingers, said opening being of a circumference smaller than a circumference of said head, whereby said head can fit inside said space with said free ends in contact with said head, and at least a portion of said head-receiving space having a circumference which is greater than said circumference of said opening whereby, in use, when said device is lowered on to said head so that said head enters said head-receiving space through said opening, said free ends of said fingers apply pressure to and thus massage said head.



- 27. (new) The device according to claim 26, wherein each said free end of each said finger is smoothly terminated.
- 28. (new) The device according to claim 27, wherein each said free end is terminated in a bulb or ball structure.
- 29. (new) The device according to claim 26, wherein said opposite ends of said fingers terminate in or form a handle for gripping said massaging device, said handle further housing said vibrator.
- 30. (new) A head massaging device including at least:

  a plurality of resilient non-rotating fingers, said fingers each having a free end and an opposite end;

a vibrator coupled to said opposite ends whereby vibrations generated by said vibrator are transmitted along said fingers from said opposite ends to said free ends;

and a handle for receiving said opposite ends and in which is disposed said vibrator, said opposite ends fixed relative to said vibrator,

each of said fingers having a transversely extending portion immediately adjacent the handle, each said transversely extending portion being followed by a contiguous portion extending downwardly and inwardly from said transversely extending portion, said contiguous portion terminating in said free end, said intermediate length and continuous length of said fingers together defining a head-receiving space for receiving a head, said space extending between said free ends and said opposite ends and having an opening at one end formed by a juxtaposition of said free ends of said fingers, said opening having a circumference smaller than a circumference of said head, and at least a portion of said head-receiving space having a circumference which exceeds said circumference of said opening whereby, in use, when said device is lowered on to said head so that said head enters said head-receiving space through said opening, said free ends of said fingers apply pressure to and thus massage said head.

31. (new) The device according to claim 30, wherein said fingers are pliable so that the size and shape of said opening can be varied.



- 32. (new) The device according to claim 30, wherein each said free end of each said finger is smoothly terminated.
- 33. (new) The device according to claim 32, wherein each said free end is terminated in a bulb or ball structure.

Please cancel claim 5 without prejudice or disclaimer.